

AS9100 / ISO9001 Certified

Features

- RoHS compliant, wide frequency range (1 MHz to 100 MHz), 20.3x20.3 mm DIP Package
- AT-cut or SC-cut Crystal, Stratum III or better stability, 15 pF HCMOS square wave or 50 Ohms sinewave output
- Voltage control option, Industry standard lead spacing
- Standard frequencies: 10, 12, 12.8, 13, 14.4, 16.384, 32.768, 100 MHz

Specifications

Frequency Stability vs. Temperature	± 20 ppb; ± 50 ppb; ± 100 ppb; ± 500 ppb;
Temperature Range	0° C to 70° C; -40° C to 85° C; -20° C to 70° C
Aging (after 30 days, 10MHz)	1E-07 first year
Initial Tolerance	± 0.5 ppm Typical, at 25° C, $V_c = 1/2 V_{cc}$
Frequency vs. Load	± 0.02 ppm Typical / $\pm 5\%$ load change
Frequency vs. Voltage	± 0.02 ppm/V Typical

G-Sensitivity	± 0.002 ppm/G, Worst direction
Input Voltage (Vcc)	+5 V $\pm 5\%$; +3.3 V $\pm 5\%$
Input Current (Max) Steady state:	200 mA at 25° C; Start-up: 500 mA

Warm-up Time 3 minutes maximum, to ± 0.1 ppm accuracy

Electrical Tuning

EFC Range	± 5 ppm/AT-cut, ± 0.7 ppm/SC-cut, with control voltage $V_c = 0.5V$ to $4.5V$
Linearity	$\pm 10\%$ maximum of best straight line fit
Slope	Positive
EFC Input Impedance	100 kOhms minimum

Sinewave Output

Output Waveform & Level	Sinewave, +3 dBm
Output Load	50 Ohms
Harmonics	-40 dB Typ, -30 dB minimum
Spurious	-80 dB Typ, -75 dB minimum

Phase Noise (max, 10MHz)

-100 dBc/Hz	10 Hz,
-135 dBc/Hz	100 Hz
-150 dBc/Hz	1 kHz
-155 dBc/Hz	10 kHz

HCMOS Output

Output Waveform & Level	HCMOS compatible squarewave; 40/60% duty cycleOutput
Output Load	15 pF
Logic "1" / Logic "0" Level	4.5 V / 0.5 V Typical
Rise/Fall Time (Tr/Tf)	5 ns maximum

